



DESIGNED | to inspire

REVEAL

B-Vent Gas Fireplace

# REVEAL

## Reveal the Beauty of Fire

Recreate the timelessness of a wood-burning fire with the open-hearth Reveal. Full, generous flames rise through a detailed log set, while a 3-layered burner adds intensity and depth. A clean face finish and textured brick interiors provide traditional masonry style. Make it your own and anchor your space with distinct finishing options.

Cover: Reveal shown with Bridgeport mantel, marron brown marble and bi-fold doors  
 Right: Reveal shown with custom mantel and bi-fold doors



### REVEAL SPECIFICATIONS

MODEL	FRONT WIDTH		BACK WIDTH		HEIGHT		DEPTH		VIEWING AREA	BTU/HOUR INPUT (NG)
	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING	UNIT	FRAMING		
RBV4236	41 [1041]	42 [1067]	23-3/4 [603]	42 [1067]	39-1/2 [1003]	39-3/4 [1010]	21-1/2 [546]	22 [559]	36 x 21 [914 x 533]	40,000 (NG)
RBV4842	47 [1194]	48 [1219]	29-3/4 [756]	48 [1219]	39-1/2 [1003]	39-3/4 [1010]	21-1/2 [546]	22 [559]	42 x 21 [1067 x 533]	43,000 (NG)

**LEFT SIDE VIEW**

**TOP VIEW**

**FRONT VIEW**

**RIGHT SIDE VIEW**

**FRAMING DIMENSIONS**

MODEL	A	B	C
RBV4236I	41 [1041]	36 [914]	23-3/4 [603]
RBV4842I	47 [1194]	42 [1067]	29-3/4 [756]

MODEL	A - ROUGH OPENING (WIDTH)	B - ROUGH OPENING (HEIGHT)	C - ROUGH OPENING (DEPTH)
RBV4236I	42 [1067]	39-3/4 [1010]	22 [559]
RBV4842I	48 [1219]	39-3/4 [1010]	22 [559]

Dimensions above are in inches and millimeters. Reference dimensions only. We recommend measuring individual units at installation. NOTE: Combustible material should not be installed over the face. Make sure you do NOT cover the decorative door opening. Refer to installation manual for detailed specifications on installing this product. Heat & Glo reserves the right to update units periodically. The flame and ember appearance may vary based on the type of fuel burned and the venting configuration used. Pictures in this brochure are not a true representation of the fireplace and/or flames.

The rough framing dimensions shown represent the distance from stud to stud only and do not take into consideration the addition of drywall. Please refer to installation instructions for complete specifications and drawings when installing this product. Go to [www.heatnglo.com](http://www.heatnglo.com) to download.

### FEATURES & BENEFITS

- 36" or 42" viewing area
- Unique, 3-level burner
- Up to 40,000 BTUs; 36" model
- Open-hearth design with optional glass doors
- Traditional or herringbone brick interiors
- Up to 43,000 BTUs; 42" model

### INTELLIFIRE™ IGNITION SYSTEM

The IntelliFire™ Ignition System (IPI) is an advanced intermittent pilot ignition system. IPI constantly monitors ignition, ensures safe functioning and conserves up to \$10/month in energy costs. To learn more, scan the code with your smartphone, or visit [heatnglo.com](http://heatnglo.com).



### FRONT OPTIONS



Glass door - non-operable    Glass door - operable

### ADDITIONAL OPTIONS NOT PICTURED

- Remote Controls & Wall Switches
- Thermal Damper
- LP Gas Conversion Kit
- Mantels and Surrounds

### VENTING

- 6" B-vent pipe

For complete information on this model, please contact us at:



No one builds a better fire

Web: [heatnglo.com](http://heatnglo.com)  
 Phone: (888) 427-3973 (952) 985-6000  
 E-mail: [info@heatnglo.com](mailto:info@heatnglo.com)

- [facebook.com/HeatandGlo](https://facebook.com/HeatandGlo)
- [twitter.com/HeatandGlo](https://twitter.com/HeatandGlo)
- [youtube.com/HeatandGlo](https://youtube.com/HeatandGlo)

### LIMITED LIFETIME WARRANTY\*

The strongest in the industry, Heat & Glo® provides a limited lifetime warranty on the most important aspects: firebox and heat exchanger.

\*For full warranty details see [heatnglo.com](http://heatnglo.com). Fireplace glass and other surfaces get extremely HOT and can cause severe burns if touched. Do not remove the protective safety screen from the front of the glass. Keep a safe distance away. To learn more visit [www.heatnglo.com/fireplacesafety](http://www.heatnglo.com/fireplacesafety)



HNG-1132U-0713